

TECHNICAL DATASHEET

ELECTRICAL SPECIFICATIONS

Item No. 154.012 / Page 1 / 3

Print Date 29.12.2025 11:37

DC-Converter 154DH-13.8-ON

230 Watt, non isolated, single output buck converter

All parameters defined on Ta=25°C, IoNom = 17.0 ADC and UiNom = 80VDC

ABSOLUTE MAXIMUM RATINGS

parameter	unit	typ
Input peak voltage	VDC	170.00
Feedback protection against overvoltage on the output	VDC	19
Output overvoltage protection	VDC	15.6

THERMAL CHARACTERISTICS

parameter	min to max	typ
Ambient temperature range	-40°C / +85°C	
Max. case temperature for thermal shut down [°C]		+90°C
Storage temperature (device not in operation)	-10°C / +65°C	
Relative maximum humidity under storage		75% RH
Storage under worst conditions [in days]		25

COMMUNICATION INTERFACE

parameter	unit	fulfilled	conditions	min to max
Option Enable (connect to Vin for operation)		✓		
Enable voltage for transformer	VDC		IoNom	18.0 to 160.0

SPECIALS

parameter	unit	fulfilled	conditions	typ
Switching frequency	kHz			125
Efficiency at light loads	%		0.25IoNom	94.00
Efficiency at medium loads	%		0.5IoNom	93.00
Efficiency at full loads	%		IoNom	93.00
MTTF	h		SN29500 @ 70°	1 000 000
For active loads or parallel connection		✓		
Drives high capacitive loads		✓		
CC/CV battery load characteristic		✓		

COMPLIANCE

parameter	fulfilled	notes
61000-6-2 (EMC-Immunity standard for industrial environment)	✓	
61000-4-2 (immunity against ESD-electrostatic discharge)	✓	
61000-4-3 (immunity High frequency electromagnetic fields)	✓	up to 50V/m
61000-4-4 (immunity against burst – electrical fast transients)	✓	
61000-4-5 (immunity against surge - high energy surges)	✓	
61000-4-6 (immunity against induced, conducted disturbances)	✓	up to 50V/m
61000-6-4 (EMC – Emission standard for industrial environment)	✓	
55022<A	✓	

All technical and general information is provided in all conscience. However, completeness and accuracy cannot be guaranteed. Demke recommends to fully test the product in its determined application. Due to permanent improvements to our products, we reserve the right to change specifications at any time and without prior notification and without obligation to update products already supplied. This is a component for professional equipment manufacturers. Read the safety and installation instruction for proper use. Safety aspect and EMC-aspect must be considered in the end application.

DEMKE
ELECTRONIC

Demke Electronic GmbH
Tonhallestrasse 37
9500 Wil - Switzerland

phone +41 71 511 34 00
e-mail sales@demke-electronic.com

web www.demke-electronic.com

DC-Converter 154DH-13.8-ON

230 Watt, non isolated, single output buck converter

INPUT

parameter	unit	conditions	min	typ	max
Input voltage range	VDC	IoNom	18	80	160
No load input current	mA	UiNom		4	
Max. input current	A	UiNom		17	
Input start up voltage	VDC	UiNom		17.0	
Undervoltage lockout	VDC	UiNom		15.0	
Input quiescent current in shutdown mode	mA	UiNom		0.60	
Input current overshoot during soft start ramp up	%	IoNom		20	
Generated AC-ripple on the supply (BW=20MHz)	mVp-p	UiNom/loNom		100	
Generated HF-noise on the supply (BW=20MHz)	mVp-p	UiNom/loNom		200	
Typical input noise slew rate (BW=500MHz)	mVp-p	UiNom/loNom		70	

OUTPUT

parameter	unit	conditions	min	typ	max
Output voltage	VDC	IoNom		13.8	
Minimum required load to obtain the specified output voltage	%	UiNom		0	
Generated AC-ripple on the output (BW=20MHz)	mVp-p	UiNom/loNom		10	
Generated HF-noise on the output (BW=20MHz)	mVp-p	UiNom/loNom		150	
Typical output noise slew rate (BW=500MHz)	mVp-p	UiNom/loNom		80	
Output voltage accuracy	%	IoNom		+/-2.00%	
Output voltage overshoot at initial switch-on	%	IoNom		overdamped	
Rated output power	W			230	

CONTROL

parameter	unit	conditions	min	typ	max
Static line regulation	%	IoNom/UiMin...UiMa		0.30	
Static load regulation	%	IoMin...IoMax/UiNo		0.4	
Dynamic load change adjusting time	ms	LoadChange 10...90		0.50	
Dynamic load change deviation to nominal output voltage	V	LoadChange 10...90		1.40	
Maximum admissible capacitive load	uF	IoNom		infinite	
Initial switch on time	ms	IoNom		90	
Softstart ramp up time	ms	IoNom		40	
Restart time after undervoltage lockout	ms	IoNom		50	

All technical and general information is provided in all conscience. However, completeness and accuracy cannot be guaranteed. Demke recommends to fully test the product in its determined application. Due to permanent improvements to our products, we reserve the right to change specifications at any time and without prior notification and without obligation to update products already supplied. This is a component for professional equipment manufacturers. Read the safety and installation instruction for proper use. Safety aspect and EMC-aspect must be considered in the end application.

DC-Converter 154DH-13.8-ON

230 Watt, non isolated, single output buck converter

MECHANICAL

parameter	unit	
Overall dimensions	mm	90x90x26
Weight	g	360


Pin No.	Function	Electrical Determination
1	On	Enable
2	Vi+	Input voltage positive
3	Vi-	Input voltage negative
4	Vo-	Output voltage negative
5	Vo+	Output voltage positive

Mechanical dimensions and Pin configuration

All dimensions in mm

Connector type: Flat pin plug 6.3mm

Case: FMC 90x90x26



All technical and general information is provided in all conscience. However, completeness and accuracy cannot be guaranteed. Demke recommends to fully test the product in its determined application. Due to permanent improvements to our products, we reserve the right to change specifications at any time and without prior notification and without obligation to update products already supplied. This is a component for professional equipment manufacturers. Read the safety and installation instruction for proper use. Safety aspect and EMC-aspect must be considered in the end application.